

SHORT BLOCK

Short Block:	Ford 302				
No. Cylinders:	8	Bore:	4.002 in	Rod Length:	4.908 in
Total Volume:	301.9 ci	Stroke:	3.000 in	Rod Ratio:	1.636

CYLINDER HEADS

Cylinder Heads: Boss 302 exch data

Valve Specifications:

Intake Valves/Port:	1	Exhaust Valves/Port:	1
Intake Valve Dia:	2.190 in	Exhaust Valve Dia:	1.730 in

COMPRESSION

Compression Ratio:	10.00		
Combustion Space:	68.71 cc	Cylinder Volume:	618.40 cc

INDUCTION

Induction Flow:	750.0 cfm @ 1.50 inHg	Fuel Type:	Gasoline
Manifold Type:	Dual-Plane High-Flow	Nitrous Injection:	0.0 lbs/min

Forced Induction Specifications:

Blower Type:	None				
Island Flow:	*** cfm	Surge Flow:	*** cfm	Pressure Ratio:	***
Impeller Speed:	*** rpm	Belt Ratio:	***	Internal Ratio:	***
Peak Efficiency:	*** %	Boost Limit:	*** psi	Intercooler:	*** %

EXHAUST

Exhaust System: Small-Tube Headers With Mufflers

CAMSHAFT

Cam Name:	Dual Purpose Street						
Intake Lift At Valve:	0.615 in	Lifter Type:	Solid				
Exhaust Lift At Valve:	0.615 in	Lifter Acceleration Rate:	3.00				
Valve Opening/Closing Based On:		0.050-Lift					
Primary Timing (0.050-inch):	IVO: 20.5	IVC: 52.5	EVO: 56.5	EVC: 16.5			
Secondary Timing (Seat-to-Seat):	IVO: ***	IVC: ***	EVO: ***	EVC: ***			
Cam Installed Advanced(+)/Retarded(-):		4.0					
True IVO:	24.5	True EVO:	60.5				
True IVC:	48.5	True ICA:	102.0	True EVC:	12.5	True ECA:	114.0
Cam Timing Summary:							
Intake Duration:	253.0	Exhaust Duration:	253.0				
Intake Centerline Angle:	106.0	Exhaust Centerline Angle:	110.0				
Lobe Centerline Angle:	108.0	Valve Overlap:	37.0				

NOTES

CYLINDER HEAD AIRFLOW DATA

Description: Boss 302 exch data

Intake Valve

Test Diameter: 2.190 in
Pressure Drop: 28.0 inH2O
Valves Per Port: 1

Lift: in Flow: cfm

0.100 73.5

0.200 146.7

0.300 203.5

0.400 244.6

0.500 270.1

0.600 279.5

*** ***

*** ***

*** ***

*** ***

Exhaust Valve

Test Diameter: 1.730 in
Pressure Drop: 28.0 inH2O
Valves Per Port: 1

Lift: in Flow: cfm

0.100 47.2

0.200 80.0

0.300 117.0

0.400 149.1

0.500 173.4

0.600 186.5

*** ***

*** ***

*** ***

*** ***

CALCULATED POWER AND ENGINE PRESSURES

Engine RPM	Power (Fly)	Torque (Fly)	Int Man Pressure	Vol Eff %	BMEP Pressure
1500	43	151	14.70	46.3	75.5
2000	89	234	14.69	61.9	117.0
2500	126	265	14.68	68.1	132.3
3000	155	272	14.66	70.7	135.8
3500	204	306	14.64	78.7	152.7
4000	256	337	14.60	86.6	168.1
4500	300	350	14.54	91.1	174.8
5000	336	353	14.49	94.2	176.3
5500	365	349	14.42	95.9	174.1
6000	381	334	14.36	94.9	166.7
6500	391	316	14.31	93.9	157.9
7000	390	292	14.26	92.0	146.1
7500	384	269	14.21	89.1	134.3
8000	366	240	14.18	86.4	120.1
8500	334	206	14.15	81.8	103.0
9000	298	174	14.14	78.5	86.8
9500	259	143	14.13	75.5	71.6
10000	219	115	14.11	71.7	57.5
10500	165	82	14.12	67.8	41.2
11000	123	59	14.13	64.7	29.4
11500	66	30	14.13	61.3	15.0



